

LED FOCO Lámpara De Calle, Parques y Exteriores



Security Light



Security Light



Security Light



Security Light



Street Light



Street Light



Explosion Proof Light



Explosion Proof Light



Street Light



Security Light



Factory



Security Light



DESIGNLIGHTS CONCEPT      



Especificaciones

Modelo	Potencia Consumo (W)	Reemplazo Lamp. Ahorrador Halogenuro Metálico	Flujo Luminoso (lm)	Color de Temperatura (K)	Índice de Reproducción de Color (Ra)	Entrada de voltaje (Vac)	Potencia Factor (P)
OBB18W	18W	45W	1,710 lm	3000 - 4000 5000 - 6000	83 ↑	100~277V	0.9 5 ↑
OBB25W	25W	63W	2,500 lm				
OBB30WF	30W	75W	3,150 lm				
OBB40WF	40W	100W	4,000 lm				
OBB45WF	45W	162W	5,400 lm				
OBB60WF	60W	216W	7,200 lm				
OBB80WF	80W	300W	10,000lm				
OBB110WF	110W	400W	14,850 lm				

Simulación

80WF ^{L+}

- Model(型号名称, 모델명, モデル) : OBB-80WF ^{L+} + 'Sejongro' Street Light Luminaire



Interval 灯间距 등간격 照明間隔	Light Installation Height : 4 m 灯具安装高度 등설치 높이 設置高さ		Light Installation Height : 6 m 灯具安装高度 등설치 높이 設置高さ	
	Average Floor Illuminance 地面平均照度 바닥평균조도 床平均照度	Uniformity 均匀度 균제도 均一性	Average Floor Illuminance 地面平均照度 바닥평균조도 床平均照度	Uniformity 均匀度 균제도 均一性
10 m	37.60 lx	U0=0.59 U1=0.64	29.30 lx	U0=0.77 U1=0.83
12 m	31.30 lx	U0=0.49 U1=0.51	24.40 lx	U0=0.7 U1=0.73

110WF ^{L2+}

- Model(型号名称, 모델명, モデル) : OBB-110WF ^{L2+} + 'Sejongro' Street Light Luminaire



Interval 灯间距 등간격 照明間隔	Light Installation Height : 4 m 灯具安装高度 등설치 높이 設置高さ		Light Installation Height : 6 m 灯具安装高度 등설치 높이 設置高さ	
	Average Floor Illuminance 地面平均照度 바닥평균조도 床平均照度	Uniformity 均匀度 균제도 均一性	Average Floor Illuminance 地面平均照度 바닥평균조도 床平均照度	Uniformity 均匀度 균제도 均一性
10 m	51.70 lx	U0=0.59 U1=0.64	40.30 lx	U0=0.77 U1=0.83
12 m	43.10 lx	U0=0.49 U1=0.51	33.60 lx	U0=0.7 U1=0.73